

GREASE HT (MS) 2

Molybdenum Disulphide Grease

Piston Power Grease HT (MS) 2 is a multi-functional, lithium soap base grease containing extreme pressure additives and 3% molybdenum disulphide.

Applications

Suitable for use in the following applications:

- Automotive
- Construction equipment
- Earthmoving, quarrying and mining
- Agricultural equipment
- Industrial equipment

Grease HT (MS) 2 can be used to lubricate the following components:

- Ball Joints and kingpins
- Constant velocity joints
- 5th wheel
- Chassis shackle pins

Performance Features

- Operating temperature range of -20°C to +150°C.
- Lessens maintenance costs. Effective EP additive protects against component wears under high load conditions.
- Reduces downtime. Excellent oxidation resistance ensures longer grease life.
- Good pumpability characteristics of the lithium thickener provide suitable flow characteristics for grease pump application systems.
- Excellent resistance to water wash out. This ensures that bearings operating in wet conditions are protected against breakdown due to rust.

Typical Characteristics

NLGI Consistency		2
Thickener		Li Complex
Colour		Black
Structure		Smooth
Worked Penetration @ 25°C	0.1mm	280
Dropping Point	°C	>250
Timken OK Load	Kg	25
Base Oil		
Kinematic Viscosity at 40°C	mm ² /s	460
Kinematic Viscosity at 100°C	mm ² /s	32