

GREASE EP (MS) 2

Molybdenun Disulphide Grease

Piston Power Grease EP (MS) 2 is a multi-functional, lithium soap base grease containing extreme pressure additives and 3% molybdenum disulphide.

Applications

Suitable for use in the following applications:

- Automotive
- Construction equipment
- Earthmoving, quarrying and mining
- Agricultural equipment
- Industrial equipment

Grease MP (EP) 2 can be used to lubricate the following components:

- Ball Joints and kingpins
- Constant velocity joints
- 5th wheel
- Chassis shackle pins

Performance Features

- Operating temperature range of -30°C to +130°C.
- Lessens maintenance costs. Effective EP additive protects against component wears under high load conditions.
- Reduces downtime. Excellent oxidation resistance ensures longer grease life.
- Good pumpability characteristics of the lithium thickener provide suitable flow characteristics for grease pump application systems.
- Excellent resistance to water wash out. This ensures that bearings operating in wet conditions are protected against breakdown due to rust.

Typical Characteristics

NLGI Consistency		2
Thickener		Lithium
Colour		Black
Structure		Smooth
Worked Penetration @ 25°C	0.1mm	280
Dropping Point	°C	175
Timken OK Load	Kg	20
Base Oil		
Kinematic Viscosity at 40°C	mm ² /s	165
Kinematic Viscosity at 100°C	mm ² /s	16